

ONDUVILLA® SLIM CAP

TECHNICAL DATA SHEET

APPLICATION

Cap for ridge and hips, offering superior aesthetics to home-owners looking for clay-tile look.

The use of the SLIM CAP requires specific accessories to secure watertightness:

- at ridge: the APRON PIECE on both sides of the roof
- at hips: ONDULAIR SLIM, our sealing tape which provides waterproofing and ventilation properties

For small roofs (< 20 m²) covering annex buildings, the use of VENTILATED FOAM FILLERS in combination with the SLIM CAP is also a possible option.

These foam fillers, which also offer ventilation properties, are available with ONDUVILLA® profile and are sold as a kit which also includes a filler for the eave.

TECHNICAL CHARACTERISTICS

Made of cellulosic fibers, natural pigments and bitumen.
Manufactured using molding process (patented technology).

Length	106 cm
Width	18 cm
Height	8 cm
Thickness	2,2 mm
Weight (pigmented/painted)	0,54 / 0,57 kg

PACKAGING

Full range matching all ONDUVILLA® colours (pigmented/painted).
Box 20 pcs
Pallet 20 boxes (400 pcs)

HANDLING AND STORAGE

The product should be protected from direct sunlight and be stored dry.

WARRANTY

Watertightness is guaranteed for 15 years.

All the claims will be considered with respect to application recommendations issued by Onduline company.

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company.

ONDULINE AVRASYA
Değirmen Sokak Nida Kule İş Mrk.
No:18 Kat:8 34742 Kozyatağı, Kadıköy/ İSTANBUL
Tel.: +90 216 384 16 00 pbx.
Fax: +90 216 384 16 10

www.onduline.com.tr



INSTALLATION

The SLIM CAP can be used for roofs with a pitch up to 120% (50°). For higher slopes, the use of our universal RIDGE PIECE A90 is recommended.

At ridge, SLIM CAPS are overlapped against prevailing winds, and appropriate overlapping distance is secured by using the embossed lines.

The SLIM CAP is fixed with Onduline nails or screws, through the corrugations of the tiles, into the roof structure.

For low pitch (<30%), soft fixing is recommended in order to avoid the possible deformation of the SLIM CAP.

The end of the ridge and hip lines is finished with the CLOSURE CAP (special type of SLIM CAP closed on one side).

For specific roof details, please refer to ONDUVILLA® fixing guide.

Onduline®